

# PURISTUSMITTATAULUKKO

16.12.2008 TER~SVAHVISTEISET KUMILETKUT

Puristusmitat on tarkastettu vain Dunlop Hi ex -tuotteille

## 122T EN 853 1SN - SAE100 R1AT



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
122T-04	110000-04-04	16,9	225
122T-05	110000-05-05	18,2	215
122T-06	110000-06-06	20,4	180
122T-08	110000-08-08	24,5	160
122T-10	110000-10-10	27,6	130
122T-12	110000-12-12	31,8	105
122T-16	110000-16-16	39,2	88
122T-20	110000-20-20	48,2	63
122T-24	110000-24-24	55,2	50
122T-32	110000-32-32	68,7	40

## 224E HYPERCOLD EN 853 2SN - SAE 100 R2AT (-55°C)



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
224E-06	220000-06-06	21,8	330
224E-08	220000-08-08	24,3	275
224E-12	220000-12-12	32,8	215

## 221T EN 857 2SC - SAE 100 R16



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
221T-04	110000-04-04	17,2	400
221T-06	110000-06-06	20,2	330
221T-08	110000-08-08	24,8	275
221T-12	110000-12-12	31,8	215

## COMMANDER EN 853 1SN - SAE100 R1AT (+150°C)



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
814AE-04	110000-04-04	16,9	225
814AE-06	110000-06-06	20,4	180
814AE-08	110000-08-08	24,5	160
814AE-10	110000-10-10	27,6	130
814AE-12	110000-12-12	31,8	105
814AE-16	110000-16-16	39,2	88
814AE-20	110000-20-20	48,2	63
814AE-24	110000-24-24	55,2	50
814AE-32	110000-32-32	68,7	40

## 241T SUPER SLIMLINE, YLITT~ EN 857 SC



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
241T-04	110000-04-04	17,2	450
241T-06	110000-06-06	20,2	350
241T-08	110000-08-08	24,8	310
241T-10	110000-10-10	27,8	280
241T-12	100000-12-12	31,8	280
241T-16	100000-16-16	40,2	225

## 241X SUPER SLIMLINE (TUFFLEX) YLITT~ EN 857 SC



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
241X-04	110000-04-04	17,2	450
241X-06	110000-06-06	20,2	350
241X-08	110000-08-08	24,8	310
241X-10	110000-10-10	27,8	280
241X-12	100000-12-12	31,8	280
241X-16	100000-16-16	40,2	225

## 141T SUPER SLIMLINE 1SN



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
141T-04	100000-04-04	15,7	280
141T-06	110000-06-06	19,9	225

## 222T EN 853 2SN - SAE 100 R2AT



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
222T-04	220000-04-04	18,3	400
222T-05	220000-05-05	19,5	350
222T-06	220000-06-06	21,8	330
222T-08	220000-08-08	24,8	275
222T-10	220000-10-10	28,3	250
222T-12	220000-12-12	32,8	215
222T-16	220000-16-16	40,8	165
222T-20	220000-20-20	51,8	125
222T-24	220000-24-24	58,9	90
222T-32	220000-32-32	71,4	80

## ALFAJET 210 PESURILETKU (+155°C)



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
8B3AE-05	H1200101-050000	17,3	210
8B3AE-06	H1200101-060000	19,4	210

## ALFAJET 400 PESURILETKU (+155°C)



Tuoteno	Holkki HITRAK	Puristusmitta mm	Työpaine bar
8B4AE-04	H1200102-040000	17,2	400
8B4AE-06	H1200212-060000	20,5	400
8B4AE-08	H1200212-080000	24,0	400

