

122T, EN 853 1SN, 1 WIRE BRAID



Product code	Ferrule HITRAK	Swaging diam. mm	Working press. bar
122T-04	110000-04-04	16,9	225
122T-05	110000-05-05	18,2	215
122T-06	110000-06-06	20,4	180
122T-08	110000-08-08	24,5	160
122T-10	110000-10-10	27,6	130
122T-12	110000-12-12	31,8	105
122T-16	110000-16-16	39,2	88
122T-20	110000-20-20	48,2	63
122T-24	110000-24-24	55,2	50
122T-32	110000-32-32	68,7	40

730G, EN 856 4SP, 4 SPIRALS



790G, EN 856 4SH, 4 SPIRALS

Product code	Ferrule SKIVABLE	Swaging diam. mm	Skive diam. mm	Working press. bar
730G-04	440000-04-04	18,5	19	450
730G-06	440000-06-06	22,1	19	445
730G-08	440000-08-08	26,4	25	415
730G-10	330000-10-10	29,2	28	350
730G-12	440000-12-12	33,3	33	380
730G-16	330000-16-16	41,3	37	320

POWERTRAK

790G-12	190000-12-12	34,5	37	420
790G-16	190000-16-16	42,5	44	380
790G-20	190000-20-20	49	48	350
790G-24	190000-24-24	56,8	60	290
790G-32	190000-32-32	72	59	250

INTERLOCK

		ins./outs. mm		
790G-12	170000-12-12	34	15/52	420
790G-16	170000-16-16	42,1	17/65	380
790G-20	170000-20-20	51,1	21,5/74	350
790G-24	170000-24-24	57,1	22/81	290
790G-32	170000-32-32	73	29/85	250

221T, EN 857 2SC, 2 WIRE BRAID



Product code	Ferrule HITRAK	Swaging diam. mm	Working press. bar
221T-04	110000-04-04	17,2	400
221T-05	110000-05-05	18,3	350
221T-06	110000-06-06	19,9	330
221T-08	110000-08-08	23,9	275
221T-10	110000-10-10	27,4	250
221T-12	110000-12-12	31,8	215
221T-16	100000-16-16	40,2	165

241T/S, EXCEEDS EN 857 2SC, SUPER SLIMLINE, 2 W.



Product code	Ferrule HITRAK	Swaging diam. mm	Working press. bar
241T-04	110000-04-04	17,2	450
241T-06	110000-06-06	20,3	350
241T-08	110000-08-08	24,5	310
241T-10	110000-10-10	27,4	280
241T-12	100000-12-12	31,8	280
241T-16	100000-16-16	40,2	225

FLEXTREME, SAE 100R13, EN 856 R13, 4 SPIRALS



Product code	Ferrule INTERLOCK	Swaging diam. mm	Skive diam. ins./outs. mm	Working press. bar
8Q9AA-12	170000-12-12	33,3	15/52	350
8Q9AA-16	170000-16-16	41,7	17/65	350

222T, EN 853 2SN, 2 WIRE BRAID



Product code	Ferrule HITRAK	Swaging diam. mm	Working press. bar
222T-04	220000-04-04	18,3	400
222T-05	220000-05-05	19,5	350
222T-06	220000-06-06	21,8	330
222T-08	220000-08-08	24,8	275
222T-10	220000-10-10	28,3	250
222T-12	220000-12-12	32,8	215
222T-16	220000-16-16	40,8	165
222T-20	220000-20-20	51,8	125
222T-24	220000-24-24	58,9	90
222T-32	220000-32-32	71,4	80

420G, SAE 100R15, 4 OR 6 SPIRALS



Product code	Ferrule INTERLOCK	Swaging diam. mm	Skive diam. ins./outs. mm	Working press. bar
420G-16	170000-16-16	42,2	17/65	420
420G-20	180000-20-20	55,8	21,5/74	420
420G-24	180000-24-24	63,6	22/81	420

224E, EN 853 2SN (HYPERCOLD), 2 W. BRAID



Product code	Ferrule HITRAK	Swaging diam. mm	Working press. bar
224E-06	220000-06-06	21,8	330
224E-08	220000-08-08	24,3	275
224E-12	220000-12-12	32,8	215

3SPG, 3 WIRE BRAID



Product code	Ferrule SKIVABLE	Swaging diam. mm	Skive diam. mm	Working press. bar
3SPG-06	440000-06-06	21,9	20	500
3SPG-08	440000-08-08	26,6	26	470
3SPG-10	330000-10-10	29,7	28	410
3SPG-12	440000-12-12	33,6	33	375
3SPG-16	330000-16-16	41,9	37	327
3SPG-20	330000-20-20	49,4	41	240